

Monupaint

Page 1/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.05.2015

Revision: 19.05.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

For professional use only

· 1.1 Product identifier For professional use only

· Trade name: **Monupaint**

· 1.2 Relevant identified uses of the substance or mixture and uses advised against Surface Coating

· Application of the substance / the mixture

Surface Coating

Surface Coating

Cellulose Topcoat

· 1.3 Details of the supplier of the safety data sheet

· Supplier:

The Blast Shop
Langley Rd
Manchester
M27 8SS

· Further information obtainable from:

· 1.4 Emergency telephone number: +44 (0)161 3516545 (Business hours)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms GHS02, GHS07, GHS08

· Signal word Danger

· Hazard-determining components of labelling:

toluene

(Contd. on page 2)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 20.05.2015

Revision: 19.05.2015

Trade name: M99 Cellulose Aerosol

(Contd. of page 1)

· Hazard statements

Extremely flammable aerosol. Pressurised container: May burst if heated.
Causes skin irritation.
Suspected of damaging the unborn child.
May cause damage to organs through prolonged or repeated exposure.
May be fatal if swallowed and enters airways.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Pressurized container: Do not pierce or burn, even after use.
IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
92.0 % by mass of the contents are flammable

· 2.3 Other hazards**· Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 115-10-6 EINECS: 204-065-8	dimethyl ether ⚠ Flam. Gas 1, H220; ⚠ Press. Gas C, H280	50-100%
CAS: 108-88-3 EINECS: 203-625-9	toluene ⚠ Flam. Liq. 2, H225; ⚠ Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	10-25%
CAS: 123-86-4 EINECS: 204-658-1	Butyl ethanoate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	2.5-10%
CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	2.5-10%
CAS: 1330-20-7 EINECS: 215-535-7	Xylene (mix) ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	2.5-10%
CAS: 67-64-1 EINECS: 200-662-2	propan-2-one ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	2.5-10%
CAS: 9004-70-0	Nitrocellulose (12.3% N) ⚠ Flam. Sol. 1, H228	2.5-10%
CAS: 78-93-3 EINECS: 201-159-0	methyl ethyl ketone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	" 2.5%
CAS: 107-98-2 EINECS: 203-539-1	1-methoxy-2-propanol ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	" 2.5%
CAS: 67-63-0 EINECS: 200-661-7	propan-2-ol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	" 2.5%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 20.05.2015

Revision: 19.05.2015

Trade name: M99 Cellulose Aerosol

(Contd. of page 2)

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Put on breathing apparatus

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/extraction at the workplace.
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Do not seal receptacle gas tight.
Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 20.05.2015

Revision: 19.05.2015

Trade name: M99 Cellulose Aerosol

(Contd. of page 3)

- Protect from heat and direct sunlight.
· 7.3 **Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm
Long-term value: 766 mg/m³, 400 ppm

108-88-3 toluene

WEL Short-term value: 384 mg/m³, 100 ppm
Long-term value: 191 mg/m³, 50 ppm
Sk

123-86-4 Butyl ethanoate

WEL Short-term value: 966 mg/m³, 200 ppm
Long-term value: 724 mg/m³, 150 ppm

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm
Long-term value: 274 mg/m³, 50 ppm
Sk

1330-20-7 Xylene (mix)

WEL Short-term value: 441 mg/m³, 100 ppm
Long-term value: 220 mg/m³, 50 ppm
Sk; BMGV

67-64-1 propan-2-one

WEL Short-term value: 3620 mg/m³, 1500 ppm
Long-term value: 1210 mg/m³, 500 ppm

78-93-3 methyl ethyl ketone

WEL Short-term value: 899 mg/m³, 300 ppm
Long-term value: 600 mg/m³, 200 ppm
Sk, BMGV

107-98-2 1-methoxy-2-propanol

WEL Short-term value: 560 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm
Sk

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm
Long-term value: 999 mg/m³, 400 ppm

- **Ingredients with biological limit values:**

1330-20-7 Xylene (mix)

BMGV 650 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: methyl hippuric acid

78-93-3 methyl ethyl ketone

BMGV 70 µmol/L
Medium: urine
Sampling time: post shift
Parameter: butan-2-one

(Contd. on page 5)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 20.05.2015

Revision: 19.05.2015

Trade name: M99 Cellulose Aerosol

(Contd. of page 4)

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
- **Respiratory protection:** When spraying the product, use a respiratory protective device.
- **Protection of hands:**
When skin exposure may occur, advice should be sought from the glove supplier on appropriate types and usage times for this product.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**
- **Form:** Aerosol
- **Colour:** According to product specification
- **Odour:** Characteristic
- **Odour threshold:** Not determined.
- **pH-value:** Not determined.
- **Change in condition**
- **Melting point/Melting range:** Undetermined.
- **Boiling point/Boiling range:** -24 °C
- **Flash point:** -42 °C
- **Flammability (solid, gaseous):** Not applicable.
- **Ignition temperature:** 235 °C
- **Decomposition temperature:** Not determined.
- **Self-igniting:** Product is not selfigniting.
- **Danger of explosion:** Heating may cause an explosion.

(Contd. on page 6)

-GB-

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 20.05.2015

Revision: 19.05.2015

Trade name: M99 Cellulose Aerosol

(Contd. of page 5)

· Explosion limits:	
Lower:	1.2 Vol %
Upper:	18.6 Vol %
· Vapour pressure at 20 °C:	5200 hPa
· Density at 20 °C:	0.775 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	NOT MISCIBLE
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	89.4 %
Solids content:	11.5 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**

· **LD/LC50 values relevant for classification:**

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rab)
Inhalative	LC50/4 h	5320 mg/l (mus)

- **Primary irritant effect:**
- **Skin corrosion/irritation** No irritant effect.
- **Serious eye damage/irritation** No irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.

· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
- Repr. 2

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 20.05.2015

Revision: 19.05.2015

Trade name: M99 Cellulose Aerosol

(Contd. of page 6)



SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---|---------------------|
| · 14.1 UN-Number | |
| · ADR, IMDG, IATA | UN1950 |
| · 14.2 UN proper shipping name | |
| · ADR | 1950 AEROSOLS |
| · IMDG | AEROSOLS |
| · IATA | AEROSOLS, flammable |
| · 14.3 Transport hazard class(es) | |
| · ADR | |
|  | |
| · Class | 2 5F Gases. |
| · Label | 2.1 |
| <hr style="border-top: 1px dashed #000;"/> | |
| · IMDG, IATA | |
|  | |
| · Class | 2.1 |
| · Label | 2.1 |
| · 14.4 Packing group | |
| · ADR, IMDG, IATA | Void |

(Contd. on page 8)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 20.05.2015

Revision: 19.05.2015

Trade name: M99 Cellulose Aerosol

(Contd. of page 7)

· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	
· Danger code (Kemler):	Warning: Gases.
· EMS Number:	-
· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	
	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· National regulations:

· Technical instructions (air):

Class	Share in %
NK	89.4

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H228 Flammable solid.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

(Contd. on page 9)

-GB-

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 20.05.2015

Revision: 19.05.2015

Trade name: M99 Cellulose Aerosol

(Contd. of page 8)

H373 May cause damage to organs through prolonged or repeated exposure.

· **Department issuing MSDS:** Product safety department: LABORATORY

· **Contact:** Health & Safety Officer

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Gas 1: Flammable gases, Hazard Category 1

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas C: Gases under pressure: Compressed gas

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Flam. Sol. 1: Flammable solids, Hazard Category 1

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

GB